



Cemat-NT 3



Cemat-NT 2



Individual blasting pressure for each chamber, 1-6 bar

## MADE IN GERMANY

Wassermann is a medium-sized, owner-operated company with head office in Hamburg. We design and produce high-quality technical devices in Germany. Our main users are dental laboratories, dental clinics and various industrial areas worldwide.

### Why a Wassermann product?

Wassermann products are manufactured from high-quality materials and the proportion of plastics used is intentionally kept as low as possible. Our devices are known for their suitability for daily use, functionality and longevity. As a result, the users place high levels of trust in the Wassermann brand. We feel it is our duty to support our customers on a daily basis when it comes to safety, service and productivity. Technological perfection, optimum quality and especially sustainability are the benchmarks we set. Thanks to the combination of these values, the family-owned company, since its establishment in 1927, has gained worldwide recognition as a manufacturer of high-quality products.



Further information are available on our website at [www.wassermann.hamburg](http://www.wassermann.hamburg)

Your Dental Dealer \_\_\_\_\_

## Cemat-NT 4, Cemat-NT 3, Cemat-NT 2



## Fine Blasting Units



Wassermann Dental-Maschinen GmbH  
Rudorffweg 15-17 · 21031 Hamburg · Germany  
Phone: +49 (0)40 730 926-0 · Fax: +49 (0)40 730 37 24  
[info@wassermann-dental.com](mailto:info@wassermann-dental.com) · [www.wassermann.hamburg](http://www.wassermann.hamburg)

# Fine Blasting Units **Cemat-NT 4,** **Cemat-NT 3 & Cemat-NT 2**

Whether sand-blasting, roughening or polishing: First-class work results are guaranteed by using the precision fine blasting units of the Cemat-NT series. These fine blasting specialists equipped with either 2 to 4 full metal blasting material tanks combine everything that can be desired of an unit of this quality - highest comfort included! Details such as the colour coding system or the optimum workspace illumination by a protected fluorescent lamp make it easy to work.

We recommend the use of Wassermann blasting materials and our low-pressure suction units **SG-10, SG-1/1** and **SG-1/2 D**.

Permanent pressure system: Prevents contamination and moisture of blasting material, genuine quick Wassermann start/stop function, noticeable low consumption of blasting material

Steady pulse-free steam, 1-6 bar, each chamber individually adjustable

With handy air blasting nozzle for easy cleaning

High quality construction, made of metal, designed for long durability

Trouble-free change of blasting materials of all common sizes possible for all chambers without use of tools

Individual pneumatic blasting control via tactile contact directly on the handpiece

Sand drawer for catching coarse of materials to relieve filters



## Major Features

- Multifunctional fine blasting units with 2 to 4 chambers
- With plug socket, e.g. for a suction unit
- High hygiene standard because of changeable sleeves
- Special particularly durable hoses
- Comfortably to handle with ergonomically shaped handpieces
- Convenient colour coding system
- Specially coated safety screen for ideal visibility
- **Included in delivery:**

Compressed air hose, 2 m

Supply line

**Cemat-NT 4** including 4 fine blasting nozzles:

0.6 (yellow), 0.8 (blue), 0.8 (red), 1.2 (green)

**Cemat-NT 3** including 3 fine blasting nozzles:

0.6 (blue), 0.8 (red), 1.2 (green)

**Cemat-NT 2** including 2 fine blasting nozzles: 0.8 (red), 1.2 (green)

Accessories	Item no.
Compressed air hose per meter	320026
Spare fine blasting nozzle 0.4 mm	190254
Spare fine blasting nozzle 0.6 mm	190250
Spare fine blasting nozzle 0.8 mm	190251
Spare fine blasting nozzle 1.2 mm	190252
<b>Cemat-NT 4</b>	<b>Item no. 190992</b>
<b>Cemat-NT 3</b>	<b>Item no. 190990</b>
<b>Cemat-NT 2</b>	<b>Item no. 190993</b>
Voltage	220–240 V / 50/60 Hz
Power consumption	0.2 A
Plug socket power consumption	max. 8 A
Output	50 W
W x H x D <b>Cemat-NT 4</b>	550 x 480 x 610 mm
W x H x D <b>Cemat-NT 3, Cemat-NT 2</b>	430 x 480 x 610 mm
Weight <b>Cemat-NT 4</b>	42.6 kg
Weight <b>Cemat-NT 3</b>	37.7 kg
Weight <b>Cemat-NT 2</b>	34.0 kg
Sound level	≤ 70 dB (A)
Tank capacity	800 cm <sup>3</sup> = 1.2 kg
Compressed air connection	3-6 bar
Working pressure	1-6 bar
Extractor nozzle	Ø 75 mm exterior